



Engine Max. Power ISO 9249 / kW/min ⁻¹	45.6 / 2 200	Engine Max. Power ISO 9249 / kW/min ⁻¹	45.6 / 2 200	Engine Max. Power ISO 9249 / kW/min ⁻¹	53.1 / 2 400	Engine Max. Power ISO 9249 / kW/min ⁻¹	96 / 2 000	Engine Max. Power ISO 9249 / kW/min ⁻¹	107 / 2 000	Engine Max. Power ISO 9249 / kW/min ⁻¹	128 / 2 200	Engine Max. Power ISO 9249 / kW/min ⁻¹	164 / 2 000	Engine Max. Power ISO 9249 / kW/min ⁻¹	179 / 2 000
Bucket Capacity / m ³	0.7 - 0.85	Bucket Capacity / m ³	0.7 - 1.05	Bucket Capacity / m ³	0.9 - 1.2	Bucket Capacity / m ³	1.5 - 2.4	Bucket Capacity / m ³	1.9 - 2.6	Bucket Capacity / m ³	2.5 - 3.1	Bucket Capacity / m ³	2.4 - 3.5	Bucket Capacity / m ³	2.8 - 3.8
Operating Weight / kg	5 140	Operating Weight / kg	5 340	Operating Weight / kg	6 280	Operating Weight / kg	11 080	Operating Weight / kg	12 220	Operating Weight / kg	14 450	Operating Weight / kg	17 930	Operating Weight / kg	20 280
Travel Speed / km/h	20.0	Travel Speed / km/h	20.0	Travel Speed / km/h	20.0	Travel Speed / km/h	39.0	Travel Speed / km/h	39.0	Travel Speed / km/h	38.0	Travel Speed / km/h	36.5	Travel Speed / km/h	36
Breakout Force / kN	42.3	Breakout Force / kN	42.3	Breakout Force / kN	54.0	Breakout Force / kN	92.0	Breakout Force / kN	98.8	Breakout Force / kN	119	Breakout Force / kN	153.9	Breakout Force / kN	165.6
Static Tipping Load (Straight) / kgf	3 750	Static Tipping Load (Straight) / kgf	3 880	Static Tipping Load (Straight) / kgf	4 235	Static Tipping Load (Straight) / kgf	8 320	Static Tipping Load (Straight) / kgf	9 210	Static Tipping Load (Straight) / kgf	11 700	Static Tipping Load (Straight) / kgf	14 600	Static Tipping Load (Straight) / kgf	16 350
Static Tipping Load (Full turn) / kgf	3 200	Static Tipping Load (Full turn) / kgf	3 305	Static Tipping Load (Full turn) / kgf	3 560	Static Tipping Load (Full turn) / kgf	7 200	Static Tipping Load (Full turn) / kgf	7 960	Static Tipping Load (Full turn) / kgf	10 110	Static Tipping Load (Full turn) / kgf	12 650	Static Tipping Load (Full turn) / kgf	14 100
Width over tire / mm	1 735	Width over tire / mm	1 760	Width over tire / mm	1 885	Width over tire / mm	2 440	Width over tire / mm	2 500	Width over tire / mm	2 490	Width over tire / mm	2 820	Width over tire / mm	2 870
Height / mm	2 480	Height / mm	2 490	Height / mm	2 575	Height / mm	3 245	Height / mm	3 265	Height / mm	3 285	Height / mm	3 370	Height / mm	3 400

ZW 310

ZW 330

ZW 370

ZW 550

ZW PL

ZW high lift



	ZW 310	ZW 330	ZW 370	ZW 550	ZW PL	ZW high lift
Engine Max. Power ISO 9249 / kW/min ⁻¹	220 / 1 800	242 / 1 800	268 / 2 000	360 / 1 800	ZW 140PL 96 / 2 000	ZW 150PL 107 / 2 000
Bucket Capacity / m ³	3.2 - 4.5	3.9 - 5.0	4.3 - 7.5	6.0 - 10.1	ZW 180 128 / 2 200	ZW 220 164 / 2 000
Operating Weight / kg	23 450	26 020	30 730	46 210	ZW 180PL 15 380	ZW 250 20 390
Travel Speed / km/h	35.5	35.5	34.8	36	ZW 310 220 / 1800	ZW 310 220 / 1800
Breakout Force / kN	186.2	226	245	377	ZW 180PL 108.6	ZW 250 163
Static Tipping Load (Straight) / kgf	19 200	19 305	23 490	29 780	ZW 180PL 10 240	ZW 250 13 300
Static Tipping Load (Full turn) / kgf	16 600	16 840	19 260	24 950	ZW 180PL 8 820	ZW 250 11 400
Width over tire / mm	2 965	3 000	3 220	3 570	ZW 180PL 2 490	ZW 250 2 870
Height / mm	3 460	3 550	3 760	4 170	ZW 180PL 3 285	ZW 250 3 400



KL-EN032EU Printed in the Netherlands